

GISELE FREE-STANDING BATH FILLER INSTALLATION INSTRUCTIONS

ATTENTION PLUMBER

To ensure the optimum performance and customer satisfaction please adhere to the following:

- Flush out all pipe work prior to installation
- Installation shall be in accordance with the AS/NZS3500 series of standards.
 The maximum operating pressure within any building should not exceed 500kpa.
 Pressure above 500kpa can cause damage from water hammer, reducing life of appliances, taps and fittings and cause excessive noise in the plumbing system.
- Pressure over 500kPa will require a limiting valve.
- Inline filters must be installed on both hot and cold supplies.

TECHNICAL DATA

Suitable for use with high pressure water supply only.
 Not suitable for gravity-fed water heaters, low and unequal pressure networks.

Minimum Water pressure for satisfactory operation: 150kPaMaximum Water pressure: 500kPa

Maximum hot water temperature: 70°C
 If the Water temperature exceeds 70°C an approved Tempering Valve must be fitted.

- Non return valve fitted in hand held outlet.
- The flow rate has been rated under the NZ Water Efficiency Labeling Scheme (WELS).

Please leave this form with the product once installed.

For full warranty terms and conditions, please see the warranty card enclosed with this product or visit $\underline{\text{www.greenstapware.com/warranty-and-care/}}$

Please contact country of purchase.

NZ:

Distributed by: Greens Global Limited

PO Box 5055, Hamilton, 3200

22 The Boulevard, Te Rapa, Hamilton 3200 Phone: 07 849 0109, Fax: 07 849 0540 Website: www.greenstapware.com

Email: nzsales@greenstapware.com Service Hotline: 0800 655 455

Distributed by: Greens Global AUS PTY LTD

36 Naxos Way, Keysborough VIC 3173 Phone: 1800 244 487 Fax: 1800 244 212 Email: aussales@greenstapware.com Website: www.greenstapware.com Service Hotline: 1800 244 992

#42034 06/21



